



The new KATKO KU 160 A Load Break Switch offers a complete modular solution.

It allows seamless installation according to the most demanding user configurations.

SWITCH ON SAFETY





- Lockable to off-position
- Modular design
- Easy configuration of multiple solutions
- Switching speed is independent of the operator
- Silver contacts ensure safe and durable operation

Type		AC-21		AC-22		AC-23		AC-23		EAN code		Weight	
		415 V		415 V									
		690 V		690 V		415 V		690 V					
		I _n / A		I _n / A		I _n / A	P / kW	I _n / A	P / kW	6419410...		kg	
3 poles	6 poles									3 poles	6 poles	3 poles	6 poles
KU 3100	KU 6100	125 A		100 A		100 A	55 kW	63 A	55 kW	...203484	...203521	0,45	0,97
KU 3125	KU 6125	160 A		125 A		125 A	55 kW	80 A	75 kW	...203491	...203538	0,45	0,97
KU 3160	KU 6160	160 A		160 A		160 A	90 kW	100 A	90 kW	...203507	...203545	0,45	0,97
KU 3100 CO	-	125 A		100 A		100 A	55 kW	63 A	55 kW	...203583	-	0,97	-
KU 3125 CO	-	160 A		125 A		125 A	55 kW	80 A	75 kW	...203590	-	0,97	-
KU 3160 CO	-	160 A		160 A		160 A	90 kW	100 A	90 kW	...203606	-	0,97	-
4 poles	8 poles									4 poles	8 poles	4 poles	8 poles
KU 4100	KU 8100	125 A		100 A		100 A	55 kW	63 A	55 kW	...203675	...203552	0,59	1,18
KU 4125	KU 8125	160 A		125 A		125 A	55 kW	80 A	75 kW	...203682	...203569	0,59	1,18
KU 4160	KU 8160	160 A		160 A		160 A	90 kW	100 A	90 kW	...203514	...203576	0,59	1,18
KU 4100 CO	-	125 A		100 A		100 A	55 kW	63 A	55 kW	...203613	-	1,18	-
KU 4125 CO	-	160 A		125 A		125 A	55 kW	80 A	75 kW	...203620	-	1,18	-
KU 4160 CO	-	160 A		160 A		160 A	90 kW	100 A	90 kW	...203637	-	1,18	-